



trutex

digital printing textiles

Mehmet Nesih Özmen Mh. Savur Sk. No:22
Merter - Güngören - İstanbul / Turkey
P. +90 212 637 76 68 | F. +90 212 637 03 38

www.tekstilbox.com

SPEEDY / Trutex 107

TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	190 gr/m ²
WIDTH	160 - 260 - 320 cm
WHITENESS	>100
TYPE	UV / Latex / ECO Solvent / Sublimation Transfer
FLAME RETARDANCY	DIN 4102 B1 / NFPA 701 / BS 5867 Part 2 Type B
APPLICATIONS	Lightbox, Display Frame Systems, Pop-up Display Systems, Blow-ups



* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job

** Latex Ink backlight results are limited

The information is based on the evaluation of carefully performed tests and practical experience.

Due to the different conditions occurring during printing, test prints should be made.

A binding assurance of the properties can not to be given for the reasons mentioned above.

LIGHTBOX P / Trutex 131

TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	130 gr/m ²
WIDTH	320 cm
WHITENESS	>100
TYPE	UV / Latex / Solvent
FLAME RETARDANCY	M1 / B1 / CA 1237 Sm / NFPA 701
APPLICATIONS	Lightbox, Display Frame Systems



* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job

** Latex Ink backlight results are limited

The information is based on the evaluation of carefully performed tests and practical experience.

Due to the different conditions occurring during printing, test prints should be made.

A binding assurance of the properties can not to be given for the reasons mentioned above.

LIGHTBOX / Trutex 138

TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	120 gr/m ²
WIDTH	320 cm
WHITENESS	>100
TYPE	UV / Latex
FLAME RETARDANCY	DIN 4102-1 B1 / NFPA 701 Test1
APPLICATIONS	Lightbox, Display Frame Systems



* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job

** Latex Ink backlight results are limited

The information is based on the evaluation of carefully performed tests and practical experience.

Due to the different conditions occurring during printing, test prints should be made.

A binding assurance of the properties can not to be given for the reasons mentioned above.

RAPIDO / Trutex 108

TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	190 gr/m ²
WIDTH	160 - 260 - 320 cm
WHITENESS	>100
TYPE	UV / Latex / ECO Solvent / Sublimation Transfer
APPLICATIONS	Lightbox, Display Frame Systems, Outdoor, Blow-ups



* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job

** Latex Ink backlight results are limited

The information is based on the evaluation of carefully performed tests and practical experience.

Due to the different conditions occurring during printing, test prints should be made.

A binding assurance of the properties can not to be given for the reasons mentioned above.

LUNA / Trutex 144

TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	120 gr/m ²
WIDTH	320 cm
WHITENESS	>100
TYPE	UV / Latex
APPLICATIONS	Lightbox, Display Frame Systems



UNIVERSAL / Trutex 126

TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	185 gr/m ²
WIDTH	310 - 505 cm
WHITENESS	>100
TYPE	UV / Latex / Solvent
FLAME RETARDANCY	DIN EN 13501-1 / B-s1, d0
APPLICATIONS	Lightbox, Display Frame Systems



PHOTO 185 / Trutex 124

TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	185 gr/m ²
WIDTH	315 cm
WHITENESS	>100
TYPE	UV / Latex / ECO Solvent
APPLICATIONS	Display frame system, Advertising banner



ELASTO / Trutex 112

TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	245 gr/m ²
WIDTH	310 cm
WHITENESS	>130
TYPE	Sublimation Direct / Sublimation Transfer / Latex
FLAME RETARDANCY	DIN 4102 B1 / NFPA 701 / BS 5867 Part 2 Type B
APPLICATIONS	Elastic Decoration, Chair Covers, Covering curved frame



DSP-180 / Trutex 104

TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	185 gr/m ²
WIDTH	320 cm
WHITENESS	>130
TYPE	Sublimation Direct / Sublimation Transfer / Latex
FLAME RETARDANCY	DIN 4102 B1 / NFPA 701 / BS 5867 Part 2 Type B
APPLICATIONS	Display frame system, Advertising banner



MICRO SATIN / Trutex 102

TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	155 gr/m ²
WIDTH	310 cm
WHITENESS	>130
TYPE	Sublimation Direct / Sublimation Transfer / Latex
FLAME RETARDANCY	DIN 4102 B1 / NFPA 701 / BS 5867 Part 2 Type B
APPLICATIONS	Lightbox, Display Frame Systems



* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job
The information is based on the evaluation of carefully performed tests and practical experience.
Due to the different conditions occurring during printing, test prints should be made.
A binding assurance of the properties can not to be given for the reasons mentioned above.

MICRO SATIN UNIVERSAL / Trutex 109

TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	165 gr/m ²
WIDTH	310 cm
WHITENESS	>120
TYPE	UV / Latex / Sublimation Transfer / Sublimation Direct
FLAME RETARDANCY	DIN 4102 B1 / NFPA 701 / BS 5867 Part 2 Type B
APPLICATIONS	Lightbox, Display Frame Systems



* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job

** Latex Ink backlight results are limited

The information is based on the evaluation of carefully performed tests and practical experience.

Due to the different conditions occurring during printing, test prints should be made.

A binding assurance of the properties can not to be given for the reasons mentioned above.

MICRO DOUBLE SATIN / Trutex 111

TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	250 gr/m ²
WIDTH	310 cm
WHITENESS	>145
TYPE	UV / Latex / Sublimation Transfer / Sublimation Direct
FLAME RETARDANCY	DIN 4102 B1 / NFPA 701 / BS 5867 Part 2 Type B
APPLICATIONS	Lightbox, Display Frame Systems, Projection Front



* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job
The information is based on the evaluation of carefully performed tests and practical experience.
Due to the different conditions occurring during printing, test prints should be made.
A binding assurance of the properties can not to be given for the reasons mentioned above.

FLAG / Trutex 125

TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	115 gr/m ²
WIDTH	320 cm
WHITENESS	>150
TYPE	Sublimation Direct / Sublimation Transfer
FLAME RETARDANCY	DIN 4102 B1 / NFPA 701 / BS 5867 Part 2 Type B
APPLICATIONS	Flag

SUB
Direct

SUB
Transfer



PREMIUM CANVAS / Trutex 113

TECHNICAL SPECIFICATIONS

COMPOSITION	55% Cotton, 45% Polyester
WEIGHT	310 gr/m ²
WIDTH	310 cm
WHITENESS	>85
TYPE	UV / Latex
APPLICATIONS	Framed artwork, art reproduction



* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job

** Latex Ink backlight results are limited

The information is based on the evaluation of carefully performed tests and practical experience.

Due to the different conditions occurring during printing, test prints should be made.

A binding assurance of the properties can not to be given for the reasons mentioned above.

FLASH ULTRA / Trutex 120

TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	210 gr/m ²
WIDTH	260-310-320 cm
WHITENESS	>130
TYPE	UV / Latex / Sublimation Transfer / Sublimation Direct
FLAME RETARDANCY	DIN 4102 B1 / NFPA 701 / BS 5867 Part 2 Type B
APPLICATIONS	Lightbox, Display Frame Systems



* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job
The information is based on the evaluation of carefully performed tests and practical experience.
Due to the different conditions occurring during printing, test prints should be made.
A binding assurance of the properties can not to be given for the reasons mentioned above.

BLACKBACK SOFT / Trutex 123

TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	240 gr/m ²
WIDTH	160-260-320 cm
WHITENESS	>90
TYPE	UV / Latex / ECO Solvent
FLAME RETARDANCY	DIN 4102 B1 / NFPA 701 / BS 5867 Part 2 Type B
APPLICATIONS	Frame systems with black backside



* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job

** Latex Ink backlight results are limited

The information is based on the evaluation of carefully performed tests and practical experience.

Due to the different conditions occurring during printing, test prints should be made.

A binding assurance of the properties can not to be given for the reasons mentioned above.

BLACKBACK DISPLAY / Trutex 121

TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	310 gr/m ²
WIDTH	155 cm
WHITENESS	>130
TYPE	Sublimation Direct / Sublimation Transfer / Latex
FLAME RETARDANCY	DIN 4102 B1 / NFPA 701 / BS 5867 Part 2 Type B
APPLICATIONS	Frame systems with black backside



* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job

** Latex Ink backlight results are limited

The information is based on the evaluation of carefully performed tests and practical experience.

Due to the different conditions occurring during printing, test prints should be made.

A binding assurance of the properties can not to be given for the reasons mentioned above.

GRAYBACK FOLD / Trutex 122

TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	290 gr/m ²
WIDTH	155 cm
WHITENESS	>130
TYPE	Sublimation Direct / Sublimation Transfer / Latex
FLAME RETARDANCY	DIN 4102 B1 / NFPA 701 / BS 5867 Part 2 Type B
APPLICATIONS	Frame systems with grey backside



* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job

** Latex Ink backlight results are limited

The information is based on the evaluation of carefully performed tests and practical experience.

Due to the different conditions occurring during printing, test prints should be made.

A binding assurance of the properties can not to be given for the reasons mentioned above.