



trutex

digital printing textiles

Mehmet Nesih Özmen Mh. Savur Sk. No:22/2
Merter - Güngören - İstanbul / Turkey
P. +90 212 637 76 68 | F. +90 212 637 03 38
www.tekstilbox.com



Rapido N-FR / Trutex 150

trutex
digital printing textiles



RAPIDO N-FR / Trutex 150

TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	180 gr/m ² (± 5%)
WIDTH	320-505 cm
WHITENESS	>100
TYPE	UV / Latex
FLAME RETARDANCY	B1
APPLICATIONS	Lightbox, Display Frame Systems, Pop up Display Systems, Inflatables, Tents, Parasols





Rapido N / Trutex 149

trutex
digital printing textiles



RAPIDO N / Trutex 149

TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	180 gr/m ² (± 5%)
WIDTH	110-260-320 cm
WHITENESS	>100
TYPE	UV / Latex
FLAME RETARDANCY	-
APPLICATIONS	Lightbox, Display Frame Systems, Pop up Display Systems, Inflatables, Tents, Parasols





Rapido N-505 / Trutex 149

trutex
digital printing textiles



RAPIDO N-505 / Trutex 149

TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	180 gr/m ² (± 5%)
WIDTH	505 cm
WHITENESS	>100
TYPE	UV / Latex
FLAME RETARDANCY	-
APPLICATIONS	Lightbox, Display Frame Systems, Pop up Display Systems, Inflatables, Tents, Parasols





Rapido Transfer / Trutex 147

trutex
digital printing textiles



RAPIDO TRANSFER / Trutex 147

TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	190 gr/m ² (± 5%)
WIDTH	320 cm
WHITENESS	>110
TYPE	Sublimation Direct / Sublimation Transfer / UV / Latex
FLAME RETARDANCY	DIN 4102 B1 / NFPA 701 / BS 5867 Part 2 Type B
APPLICATIONS	Lightbox, Display Frame Systems, Pop-up Display Systems, Blow-ups

SUB
Direct

SUB
Transfer

UV

Latex



* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job

** Latex Ink backlight results are limited

The information is based on the evaluation of carefully performed tests and practical experience.

Due to the different conditions occurring during printing, test prints should be made.

A binding assurance of the properties can not to be given for the reasons mentioned above.



Lightbox P / Trutex 131

trutex
digital printing textiles



LIGHTBOX P / Trutex 131

TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	130 gr/m ² (± 5%)
WIDTH	320 cm
WHITENESS	>100
TYPE	UV / Latex / Solvent
FLAME RETARDANCY	M1 / B1 / CA 1237 Sm / NFPA 701
APPLICATIONS	Lightbox, Display Frame Systems



* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job

** Latex Ink backlight results are limited

The information is based on the evaluation of carefully performed tests and practical experience.

Due to the different conditions occurring during printing, test prints should be made.

A binding assurance of the properties can not to be given for the reasons mentioned above.



Micro Double Satin / Trutex 111

trutex
digital printing textiles



MICRO DOUBLE SATIN / Trutex 111

TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	250 gr/m ² (± 5%)
WIDTH	310 cm
WHITENESS	>145
TYPE	Sublimation Transfer / Sublimation Direct
FLAME RETARDANCY	DIN 4102 B1 / NFPA 701 / BS 5867 Part 2 Type B
APPLICATIONS	Lightbox, Display Frame Systems, Projection Front

SUB
Direct

SUB
Transfer



* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job
The information is based on the evaluation of carefully performed tests and practical experience.
Due to the different conditions occurring during printing, test prints should be made.
A binding assurance of the properties can not to be given for the reasons mentioned above.



Micro Satin / Trutex 102

trutex
digital printing textiles



MICRO SATIN / Trutex 102

TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	155 gr/m ² (± 5%)
WIDTH	152-255-310 cm
WHITENESS	>130
TYPE	Latex / Sublimation Transfer / Sublimation Direct
FLAME RETARDANCY	DIN 4102 B1 / NFPA 701 / BS 5867 Part 2 Type B / M1*
APPLICATIONS	Lightbox, Display Frame Systems

Latex

SUB
Direct

SUB
Transfer



* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job

** Latex Ink backlight results are limited

The information is based on the evaluation of carefully performed tests and practical experience.

Due to the different conditions occurring during printing, test prints should be made.

A binding assurance of the properties can not to be given for the reasons mentioned above.



Flash Ultra / Trutex 120

trutex
digital printing textiles



FLASH ULTRA / Trutex 120

TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	210 gr/m ² (± 5%)
WIDTH	260-310-320 cm
WHITENESS	>130
TYPE	UV / Latex / Sublimation Transfer / Sublimation Direct
FLAME RETARDANCY	DIN 4102 B1 / NFPA 701 / BS 5867 Part 2 Type B
APPLICATIONS	Lightbox, Display Frame Systems



* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job
The information is based on the evaluation of carefully performed tests and practical experience.
Due to the different conditions occurring during printing, test prints should be made.
A binding assurance of the properties can not to be given for the reasons mentioned above.



Photo 185 / Trutex 124

trutex
digital printing textiles



PHOTO 185 / Trutex 124

TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	185 gr/m ² (± 5%)
WIDTH	315 cm
WHITENESS	>100
TYPE	UV / Latex / ECO Solvent
APPLICATIONS	Display frame system, Advertising banner





DSP 180 / Trutex 104

trutex
digital printing textiles



DSP-180 / Trutex 104

TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	185 gr/m ² (± 5%)
WIDTH	315 cm
WHITENESS	>130
TYPE	Sublimation Direct / Sublimation Transfer / Latex
FLAME RETARDANCY	DIN 4102 B1 / NFPA 701 / BS 5867 Part 2 Type B
APPLICATIONS	Display frame system, Advertising banner





DSP 210 / Trutex 105

trutex
digital printing textiles



DSP-210 / Trutex 105

TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	210 gr/m ² (± 5%)
WIDTH	315 cm
WHITENESS	>140
TYPE	Sublimation Direct / Sublimation Transfer / Latex
FLAME RETARDANCY	DIN 4102 B1 / NFPA 701 / BS 5867 Part 2 Type B
APPLICATIONS	Display frame system, Advertising banner





Elasto / Trutex 112

trutex
digital printing textiles



ELASTO / Trutex 112

TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	245 gr/m ² (± 5%)
WIDTH	310 cm
WHITENESS	>130
TYPE	Sublimation Direct / Sublimation Transfer / Latex
FLAME RETARDANCY	DIN 4102 B1 / NFPA 701 / BS 5867 Part 2 Type B
APPLICATIONS	Elastic Decoration, Chair Covers, Covering curved frame





Flag / Trutex 125

trutex
digital printing textiles



FLAG / Trutex 125

TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	115 gr/m ² (± 5%)
WIDTH	320 cm
WHITENESS	>150
TYPE	Sublimation Direct / Sublimation Transfer
FLAME RETARDANCY	DIN 4102 B1 / NFPA 701 / BS 5867 Part 2 Type B
APPLICATIONS	Flag

SUB
Direct

SUB
Transfer



The information is based on the evaluation of carefully performed tests and practical experience.
Due to the different conditions occurring during printing, test prints should be made.
A binding assurance of the properties can not to be given for the reasons mentioned above.



Premium Canvas / Trutex 113

trutex
digital printing textiles



PREMIUM CANVAS / Trutex 113

TECHNICAL SPECIFICATIONS

COMPOSITION	55% Cotton, 45% Polyester
WEIGHT	310 gr/m ² (± 5%)
WIDTH	310 cm
WHITENESS	>85
TYPE	UV / Latex
APPLICATIONS	Framed artwork, art reproduction



* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job

** Latex Ink backlight results are limited

The information is based on the evaluation of carefully performed tests and practical experience.

Due to the different conditions occurring during printing, test prints should be made.

A binding assurance of the properties can not to be given for the reasons mentioned above.



Blackback Soft / Trutex 123

trutex
digital printing textiles



BLACKBACK SOFT / Trutex 123

TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	240 gr/m ² (± 5%)
WIDTH	160-260-320 cm
WHITENESS	>90
TYPE	UV / Latex / ECO Solvent
FLAME RETARDANCY	DIN 4102 B1 / NFPA 701 / BS 5867 Part 2 Type B
APPLICATIONS	Frame systems with black backside



* Uv-inks could cause curling and test prints for suitability must always be carried out before actual printing job

** Latex Ink backlight results are limited

The information is based on the evaluation of carefully performed tests and practical experience.

Due to the different conditions occurring during printing, test prints should be made.

A binding assurance of the properties can not to be given for the reasons mentioned above.



Blackback -V / Trutex 151

trutex
digital printing textiles



BLACKBACK -V / Trutex 151

TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	235 gr/m ² (± 5%)
WIDTH	320 cm
WHITENESS	>90
TYPE	Treatment applied for Sub Paper / Direct Sub. / Latex / Uv-Curable
FLAME RETARDANCY	-
APPLICATIONS	Display Roll Up System / Stage Decoration Backdrop / Frontlie / Roller Blind





ACOUSTIC / Trutex 148

TECHNICAL SPECIFICATIONS

COMPOSITION	100% Polyester
WEIGHT	220 gr/m ² (± 5%)
WIDTH	155-310 cm
WHITENESS	>120
TYPE	UV / Sublimation Transfer / Sublimation Direct / Latex
FLAME RETARDANCY	DIN 4102-1 B1
APPLICATIONS	Lightbox, Display Frame Systems

